

Dimensions shown may be changed without prior notice

// 455LE

**Fat food delivery 10 bar (150 psi)
FDA - 3-A - D.M. 21/03/73****Tube:** white NBR.**Reinforcement:** high tensile textile cords.**Cover:** blue NBR/PVC - abrasion, ozone and oil resistant.**Application:** liquid and fat food-alcoholic beverages delivery - max 75%.

Sterilize with 130 °C (266 °F) steam for 30 minutes or with 5% soda solution.

Constant operation: -30 °C +100 °C (-22 °F +212 °F)

↔		↔		↻		↻		↷		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	10	150	30	450				0,380	0,26
19,0	3/4"	31,00	1,22	10	150	30	450				0,610	0,41
25,0	1"	37,00	1,46	10	150	30	450				0,760	0,52
32,0	1 1/4"	44,00	1,73	10	150	30	450				0,930	0,63
38,0	1 1/2"	50,00	1,97	10	150	30	450				1,090	0,74
51,0	2"	65,00	2,56	10	150	30	450				1,690	1,14

// 455LL

**Fat food delivery 10 bar (150 psi)
FDA - 3-A - D.M. 21/03/73****Tube:** white NBR.**Reinforcement:** high tensile textile cords.**Cover:** white NBR/PVC - abrasion, ozone and oil resistant.**Application:** liquid and fat food-alcoholic beverages delivery - max 75%.

Sterilize with 130 °C (266 °F) steam for 30 minutes or with 5% soda solution.

Constant operation: -30 °C +100 °C (-22 °F +212 °F)

↔		↔		↻		↻		↷		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
38,0	1 1/2"	48,00	1,89	10	150	30	450				0,880	0,60
51,0	2"	63,00	2,48	10	150	30	450				1,410	0,95
76,0	3"	88,00	3,46	10	150	30	450				2,050	1,38