

// 720AA



Bulk material S&D 10 bar (150 psi)

Tube: black conductive NR - abrasion resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire.
Cover: black conductive SBR/NR - abrasion and ozone resistant.
Application: bulk material suction and delivery in heavy duty applications. Specially designed for dry cement, grain and animal feed transfer.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤵		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	65,00	2,56	10	150	30	450	153,0	6,02	100	1,430	0,97	
63,0	2 1/2"	77,00	3,03	10	150	30	450	189,0	7,44	90	1,900	1,28	
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,280	1,54	
76,0	3"	92,00	3,62	10	150	30	450	228,0	8,98	90	2,600	1,75	
90,0	3 1/2"	106,00	4,17	10	150	30	450	270,0	10,63	90	3,230	2,18	
102,0	4"	116,00	4,57	10	150	30	450	306,0	12,05	90	3,180	2,14	
102,0	4"	118,00	4,65	10	150	30	450	306,0	12,05	90	3,600	2,42	
127,0	5"	143,00	5,63	5	75	15	225	508,0	20,00	80	4,750	3,20	
127,0	5"	145,00	5,71	5	75	15	225	508,0	20,00	80	5,270	3,55	
152,0	6"	168,00	6,61	5	75	15	225	608,0	23,94	80	5,950	4,00	
203,0	8"	221,00	8,70	5	75	15	225	812,0	31,97	70	8,990	6,05	

// 7P1AA



EVOLUTION PLUS

Bulk material S&D - Square corrugated - Extra flexible

Tube: black conductive NR - abrasion resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire.
Cover: black conductive SBR/NR - abrasion and ozone resistant.
Application: bulk material suction and delivery. Special construction for maximum flexibility.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤵		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	67,00	2,64	10	150	30	450	51,0	2,01	100	1,630	1,10	
63,0	2 1/2"	80,00	3,15	10	150	30	450	126,0	4,96	90	2,240	1,51	
76,0	3"	93,00	3,66	10	150	30	450	152,0	5,98	90	2,520	1,70	
102,0	4"	121,00	4,76	10	150	30	450	204,0	8,03	90	3,730	2,51	
127,0	5"	144,00	5,67	5	75	15	225	381,0	15,00	80	5,070	3,41	
152,0	6"	169,00	6,65	5	75	10	150	456,0	17,95	80	6,300	4,24	