

// 720LA



**Bulk food S&D 10 bar (150 psi)
FDA**

Tube: white NR - abrasion resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire - antistatic wire.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: bulk food and material suction and delivery. Specially designed for grain, flour and plastic pellets transfer.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⌒		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
76,0	3"	92,00	3,62	10	150	30	450	228,0	8,98	90	2,680	1,81	
90,0	3 1/2"	106,00	4,17	10	150	30	450	270,0	10,63	90	3,330	2,24	
102,0	4"	118,00	4,65	10	150	30	450	306,0	12,05	90	3,700	2,49	

// 720LG



**Bulk food S&D 10 bar (150 psi)
FDA**

Tube: white NR - abrasion resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: green NBR/PVC - abrasion and ozone resistant.

Application: bulk food and material suction and delivery. Specially designed for grain, flour and plastic pellets transfer.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⌒		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	67,00	2,64	10	150	30	450	153,0	6,02	100	1,830	1,23	
76,0	3"	92,00	3,62	10	150	30	450	228,0	8,98	90	2,840	1,91	
102,0	4"	118,00	4,65	10	150	30	450	306,0	12,05	90	3,910	2,63	
127,0	5"	145,00	5,71	5	75	15	225	508,0	20,00	80	5,680	3,82	
152,0	6"	170,00	6,69	5	75	15	225	608,0	23,94	80	7,050	4,74	
203,0	8"	223,00	8,78	5	75	15	225	812,0	31,97	70	10,470	7,04	