

Dimensions shown may be changed without prior notice

// 760AA



Bulk material delivery 5 bar (75 psi)

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: bulk material delivery.

Specially designed for dry cement, grain and animal feed transfer.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⊙		⊙		⌒		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
75,0	3"	93,00	3,66	5	75	15	225				2,310	1,56	
90,0	3 1/2"	102,00	4,02	5	75	15	225				2,060	1,39	
90,0	3 1/2"	110,00	4,33	5	75	15	225				3,140	2,12	
100,0	4"	120,00	4,72	5	75	15	225				3,450	2,32	
102,0	4"	114,00	4,49	5	75	15	225				2,310	1,56	
102,0	4"	118,00	4,65	5	75	15	225				2,710	1,83	
102,0	4"	120,00	4,72	5	75	15	225				3,130	2,11	
110,0	4 5/16"	122,00	4,80	5	75	15	225				2,470	1,66	
127,0	5"	145,00	5,71	5	75	15	225				3,800	2,56	

// 766AA



Bulk material delivery 10 bar (150 psi)

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: bulk material delivery in heavy duty applications.

Specially designed for dry cement, grain and animal feed transfer.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⊙		⊙		⌒		⌒		⌒	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
76,0	3"	92,00	3,62	10	150	30	450				2,120	1,43	
102,0	4"	118,00	4,65	10	150	30	450				2,860	1,93	
127,0	5"	143,00	5,63	10	150	30	450				3,530	2,38	