

Dimensions shown may be changed without prior notice

// 760LA



**Bulk food delivery 5 bar (75 psi)
FDA**

Tube: white NR - abrasion resistant.
Reinforcement: high tensile textile cords - antistatic wire.
Cover: black conductive SBR/NR - abrasion and ozone resistant.
Application: bulk food and material delivery.
 Specially designed for grain, flour and plastic pellets transfer.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
75,0	3"	93,00	3,66	5	75	15	225				2,370	1,60
90,0	3 1/2"	102,00	4,02	5	75	15	225				2,120	1,43
100,0	4"	120,00	4,72	5	75	15	225				3,550	2,39
102,0	4"	120,00	4,72	5	75	15	225				3,170	2,14
110,0	4 5/16"	122,00	4,80	5	75	15	225				2,540	1,71

// 760LB



**Bulk food delivery 5 bar (75 psi)
FDA**

Tube: white NR - abrasion resistant.
Reinforcement: high tensile textile cords - antistatic wire.
Cover: grey SBR/EPDM - abrasion and ozone resistant.
Application: bulk food and material delivery.
 Specially designed for grain, flour and plastic pellets transfer.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
102,0	4"	118,00	4,65	5	75	15	225				3,140	2,12