

CALIKLER HT



**BULK MATERIALS
HANDLING**

Air line



APPLICATIONS

Air line from compressor/booster on all types of tanker lorries for bulk transport of powdered products.

ADVANTAGES

- † Extremely flexible with very low bending radius.
- † Suitable for all types of road tanker compressors/boosters.
- † Can be supplied fitted with swaged couplings, conforming with transported materials specifications.

TECHNICAL DESCRIPTION

Inner tube: heat resistant EPDM, white, smooth.

Reinforcement: high temperature resistant textile with embedded steel helix.

Cover: weather resistant EPDM, black, fabric impression.

Temperature range: -30 °C to +180 °C.
Peaks at +240 °C.

HT




Made in France



TRELLEBORG

CALIKLER HT





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
50.0	7 ±1	64.0 ±1.5	3	18	0.8	125	1.81	20	0060213	ı
50.0	7 ±1	64.0 ±1.5	3	18	0.8	125	1.81	40	0060212	ı
55.0	6.5 ±1	68.0 ±1.5	3	18	0.8	140	1.84	20	0200589	120
55.0	6.5 ±1	68.0 ±1.5	3	18	0.8	140	1.84	40	0200588	120
60.0	6.5 ±1	73.0 ±1.5	3	18	0.8	150	1.98	20	0070666	120
60.0	6.5 ±1	73.0 ±1.5	3	18	0.8	150	1.98	40	0070667	120
70.0	7 ±1	84.0 ±1.5	3	18	0.8	210	2.63	20	0200591	ı
70.0	7 ±1	84.0 ±1.5	3	18	0.8	210	2.63	40	0200590	120
75.0	7.5 ±1	90.0 ±1.5	3	18	0.8	225	2.96	20	0060215	ı
75.0	7.5 ±1	90.0 ±1.5	3	18	0.8	225	2.96	40	0060214	ı
89.0	7 ±1	103.0 ±1.5	3	18	0.8	310	3.26	20	0200593	ı
89.0	7 ±1	103.0 ±1.5	3	18	0.8	310	3.26	40	0200592	120

Tolerance on length: ±1% (ISO 1307 Standard).

ı Upon availability.

Digital version

